



## Material Safety Data Sheet

### Section 1: Product and Company Identification

RPM Wood Finishes Group, Inc.

Company Phone number: (800) 522-8266

P.O. Box 22000

CIEMTREC: (800) 424-9300 International: 703-527-3887 (collect)

Hickory, NC 28603

Issue Date: 01/27/2009

Product Name: WHITE W/B VACUOCOAT PRIMER

Product Code: 7-6SP16382BP5, 7-6SP16382WPTT

### Section 2: Hazards Identification

#### EMERGENCY OVERVIEW

Appearance: Colored Viscous Liquid

Odor: Mild Amine

Principal Hazards: WARNING!

Causes eye and skin irritation. Harmful if swallowed. May be harmful if absorbed through skin. Vapor harmful.

Potential Health Effects: See Section 11 for more information.

Primary Routes of Exposure: Eye contact, ingestion, skin contact, inhalation, and absorption.

#### Eye Contact:

Product may cause eye irritation; signs and symptoms may include a burning sensation, redness, tearing, inflammation, blurred vision, and/or possible transient corneal injury.

#### Ingestion:

If ingested, product may cause irritation of mouth, throat, stomach, and digestive and central nervous systems; signs and symptoms may include headache, drowsiness, dizziness, swelling, abdominal discomfort, and/or burning sensation.

#### Skin Contact:

May be harmful if absorbed through the skin. Product may cause skin irritation; signs and symptoms may include drying, cracking, sensitization, reddening, discoloration, blistering and/or swelling.

#### Inhalation:

Product if inhaled may cause severe irritation or damage (including but not limited to burns, scarring, and ulcerization) to respiratory tract and central nervous system. Signs and symptoms may include weakness, headache, drowsiness, dizziness, swelling, abdominal discomfort, burning sensation, shock or collapse, convulsions, breathing difficulties, nasal perforation, ulceration, heart damage, blindness, bleeding and/or death. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Issue Date: 01/27/2009

Page 1 of 9

File: 17-6SP16382WPTT\_MSDS\_ENGUSA\_003.pdf

**Material Safety Data Sheet****Product Name:** WHITE W/B VACUCOAT PRIMER**Target Organs:** Not Determined**Carcinogenicity:** This product contains carcinogens or potential carcinogens as listed by IARC or NTP.**Hazardous Listing:** Components of this product are considered hazardous per the OSHA Hazard Communication Standard (29 CFR 1910.1200).**Section 3: Composition/Information on Ingredients**

Chemical	CAS	Percent Composition
water	7732-18-5	30 - 50
titanium dioxide	13463-67-7	10 - 20
hydrous calcium magnesium silicate mixture	proprietary	1 - 10
aluminum silicate	1332-58-7	1 - 10
calcium carbonate	471-34-1	1 - 10
magnesium silicate hydrate	14807-96-6	1 - 10
vinyl acetate	9003-20-7	1 - 10
isopropanol	67-63-0	1 - 10
butyl cellosolve	111-76-2	1 - 10
aluminum hydroxide	21645-51-2	< 1
wetting agent solids	proprietary	< 1
petroleum distillate	64742-54-7	< 1
aluminum oxide	1344-28-1	< 1
alkyl phenol surfactant	60864-33-7	< 1
silica	7631-86-9	< 1
crystalline silica	14808-60-7	< 1
butyl benzyl phthalate	85-68-7	< 1
polyethylene glycol phenyl ether	9036-19-5	< 0.1
additive solids	proprietary	< 0.1
vinyl acetate monomer	108-05-4	< 0.1
surfactant	proprietary	< 0.1
acrylic polymer	proprietary	< 0.1
acetylenic diol	126-86-3	< 0.1
propylene glycol	57-55-6	< 0.1
triethanolamine	102-71-6	< 0.1

**Section 4: First Aid Measures****Eye Contact:**

If exposure occurs, flush the affected eye for at least 20 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention immediately after flushing.

Issue Date: 01/27/2009

Page 2 of 9

File: I7-6SP16382WPTT\_MSDS\_ENGUSA\_003.pdf

**Material Safety Data Sheet****Product Name:** WHITE W/B VACUOCOAT PRIMER

---

**Ingestion:**

Do not induce vomiting. Dilute with water or milk. Never give fluids if the victim is unconscious or having convulsions. Seek medical attention immediately. Contact Poison Control Center immediately.

**Skin Contact:**

If exposure occurs, flush the affected area thoroughly with water for at least 15 minutes. Destroy contaminated clothing and shoes. Seek medical attention immediately.

**Inhalation:**

Remove to fresh air. If not breathing, administer CPR until help arrives or the victim starts to breathe on his own. If breathing is difficult, give oxygen. Seek medical attention immediately.

**Section 5: Fire Fighting Measures****Extinguishing Media:**

This product is not expected to burn under normal conditions of use.

**Products of Combustion:**

Combustion may produce carbon monoxide, carbon dioxide, and irritating or toxic vapors and gases.

**Protection of Firefighters / Explosion Hazards:**

Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**Section 6: Accidental Release Measures**

Follow personal protective equipment recommendations found in Section 8. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage systems or open waterways.

**Material Safety Data Sheet****Product Name:** WHITE W/B VACUOCOAT PRIMER**Section 7: Handling and Storage****Handling:**

Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition.

**Storage:**

Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

**Section 8: Exposure / Personal Protection**

OSHA 29 CFR 1910.1000 Air Contaminants – Tables:

Chemical	CAS	Z-1 PEL (units as noted)	Z-2 PEL (PPM)	Z-3 Status	Specifically Regulated see:	ACGIH TLV (units as noted)
ater	7732-18-5					
tanium dioxide	13463-67-7	15 MGM3				10 MGM3
ydrous calcium magnesium silicate mixture	proprietary					
uminum silicate	1332-58-7	5 MGM3				2 MGM3
alcium carbonate	471-34-1	15 MGM3		*		10 MGM3
agnesium silicate hydrate	14807-96-6			*		2 MGM3
nyl acetate	9003-20-7					
opropanol	67-63-0	980 MGM3 (400 PPM)				200 PPM
nyl collosolve	111-76-2	240 MGM3 (50 PPM)				20 PPM
uminum hydroxide	21645-51-2					
etting agent solids	proprietary					
stroleum distillate	64742-54-7					
uminum oxide	1344-28-1	5 MGM3				10 MGM3
nyl phenol surfactant	60864-33-7					
lica	7631-86-9			*		
ystalline silica	14808-60-7			*		0.025 MGM3
nyl benzyl phthalate	85-68-7					
lyethylene glycol phenyl ether	9036-19-5					
lditive solids	proprietary					
nyl acetate monomer	108-05-4					10 PPM
rfactant	proprietary					
rylic polymer	proprietary					
etylenic diol	126-86-3					
opolyene glycol	57-55-6					
ethanolamine	102-71-6					5 MGM3

Issue Date: 01/27/2009

File: 17-6SP16382WPTT\_MSDS\_ENGUSA\_003.pdf

Page 4 of 9

**Material Safety Data Sheet****Product Name:** WHITE W/B VACUCOAT PRIMER

---

**Engineering Controls:**

Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits.

**Eye / Face Protection:**

Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.

**Skin Protection:**

Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.

**Respiratory Protection:**

A NIOSH-approved air-purifying respirator with the appropriate cartridge may be appropriate under certain circumstances where airborne concentrations are expected to exceed permissible exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air supplied respirator if there is potential for an uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

**General Hygiene Considerations:**

It is good practice to avoid contact with the product and/or its vapor, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

**Section 9: Physical and Chemical Properties**

<b>Physical State:</b>	Colored Viscous Liquid
<b>Odor:</b>	Mild Amine
<b>Odor Threshold:</b>	Not determined.
<b>pH:</b>	Not determined.
<b>Freezing Point:</b>	Not determined.
<b>Boiling Point:</b>	Not determined.
<b>Flash Point (°F):</b>	NOT APPLICABLE
<b>Evaporation Rate:</b>	Not determined.
<b>Flammability (solid, gas):</b>	Not determined.
<b>Upper Flammability Limit:</b>	Not determined.
<b>Lower Flammability Limit:</b>	Not determined.
<b>Vapor Pressure:</b>	Not determined.
<b>Vapor Density:</b>	Not determined.

**Material Safety Data Sheet****Product Name:** WHITE W/B VACUCOAT PRIMER

---

<b>Specific Gravity:</b>	1.53
<b>Weight per Gallon (lbs):</b>	12.7
<b>Solubility (water):</b>	Not determined.
<b>Partition Coefficient (n-octanol/water):</b>	Not determined.
<b>Auto-ignition Temperature:</b>	Not determined.
<b>Coating VOC g/l:</b>	146.02
<b>Coating VOC lbs/gal:</b>	1.22
<b>Material VOC g/l:</b>	57.51
<b>Material VOC lbs/gal:</b>	0.48
<b>Solids VOL%:</b>	32.49
<b>Solids WT %:</b>	56.29

Contains Non-Photochemically Reactive Solvent.

VOC data per US EPA guidelines. Some states and localities have guidelines more stringent than federal regulations.

Aerosol coating product category codes and applicable reactivity limits are displayed on product labels per 40 CFR 59.507.

**Section 10: Stability and Reactivity****Stability:**

Stable under normal conditions.

**Conditions to Avoid/Incompatible Materials:**

Keep away from heat, sparks and flames.

**Hazardous Decomposition Products:**

Not determined.

**Material Safety Data Sheet****Product Name:** WHITE W/B VACUCOAT PRIMER

---

**Section 11: Toxicology Information**

Chemical	CAS	IARC	NTP
water	7732-18-5		
titanium dioxide	13463-67-7		
hydrous calcium magnesium silicate mixture	proprietary		
aluminum silicate	1332-58-7		
calcium carbonate	471-34-1		
magnesium silicate hydrate	14807-96-6		
vinyl acetate	9003-20-7		
isopropanol	67-63-0		
butyl cellosolve	111-76-2		
aluminum hydroxide	21645-51-2		
wetting agent solids	proprietary		
petroleum distillate	64742-54-7		
aluminum oxide	1344-28-1		
alkyl phenol surfactant	60864-33-7		
silica	7631-86-9		
crystalline silica	14808-60-7		*
butyl benzyl phthalate	85-68-7		
polyethylene glycol phenyl ether	9036-19-5		
additive solids	proprietary		
vinyl acetate monomer	108-05-4		
surfactant	proprietary		
acrylic polymer	proprietary		
acetylenic diol	126-86-3		
propylene glycol	57-55-6		
triethanolamine	102-71-6		

Toxicological evaluation of this product as a whole has not been performed. Individual components that are potential or known carcinogens are listed above.

**Section 12: Ecological Information**

Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

**Material Safety Data Sheet****Product Name:** WHITE W/B VACUCOAT PRIMER**Section 13: Disposal Considerations**

Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

**Section 14: Transportation Information****DOT Basic description:** NOT RESTRICTED

See 49 CFR 172.101 for Special Provisions, Packaging, and Quantity Limitations.

**Section 15: Regulatory Information**

Chemical Name	CAS	CERCLA	CERCLA RQ	EPCRA EHS	EPCRA TPQ	SARA 313	TSCA	DSL	EINECS	Proposition 65	WHMIS
water	7732-18-5						*	*	*		
titanium dioxide	13463-67-7						*	*	*		
hydrous calcium magnesium silicate mixture	proprietary										
aluminum silicate	1332-58-7						*	*	*		
calcium carbonate	471-34-1						*	*	*		
magnesium silicate hydrate	14807-96-6						*	*	*		
vinyl acetate	9003-20-7						*	*			
isopropanol	67-63-0					*	*	*	*		*
butyl cellosolve	111-76-2						*	*	*		*
aluminum hydroxide	21645-51-2						*	*	*		
cutting agent solids	proprietary										
petroleum distillate	64742-54-7						*	*	*		
aluminum oxide	1344-28-1					*	*	*	*		*
alkyl phenol surfactant	60864-33-7						*	*			
silica	7631-86-9						*	*	*		*
crystalline silica	14808-60-7						*	*	*	*	*
butyl benzyl phthalate	85-68-7	*	100 LBS				*	*	*	*	*
polyethylene glycol phenyl ether	9036-19-5						*	*			*
additive solids	proprietary										
vinyl acetate monomer	108-05-4	*	5000 LBS	*	1000 LBS	*	*	*	*		*
surfactant	proprietary										
acrylic polymer	proprietary										
octylenic diol	126-86-3						*	*	*		
propylene glycol	57-55-6						*	*	*		*
octhanolamine	102-71-6						*	*	*		*

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.



**Material Safety Data Sheet****Product Name:** WHITE W/B VACUCOAT PRIMER**Section 16: Other Information**

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

**HMIS Codes**      **Health** 1      **Flammability** 1      **Reactivity** 0

**Key to Abbreviations:**

*	Item appears on indicated list (or inventory)
ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service Registry Number
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CERCLA RQ	CERCLA Reportable Quantity
CFR	Code of Federal Regulations
CPR	Cardiopulmonary resuscitation
DSL	Domestic Substances List of Canada
EINECS	European Inventory of Existing Chemical Substances
EPCRA	Emergency Planning and Community Right-to-know Act
EPCRA EHS	EPCRA Extremely Hazardous Substance
EPCRA TPQ	EPCRA Threshold Planning Quantity
°F	Fahrenheit degrees
g/l	Grams per liter
gal	Gallons
IARC	International Agency for Research on Cancer
lbs or LBS	Pounds
MGM3	Milligrams per cubic meter
MIR	Maximum Incremental Reactivity
MSDS	Material Safety Data Sheet
NIOSH	National Institute of Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
PPM	Parts per million
Proposition 65	California's Safe Drinking Water and Toxic Enforcement Act
SARA	Superfund Amendments and Reauthorization Act
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
USEPA	United States Environmental Protection Agency
VOC	Volatile Organic Compound
VOL	Volume
WT	Weight
WHMIS	Canadian Workplace Hazardous Materials Information System
UN	United Nations


Issue Date: 01/27/2009  
 File: I7-6SP16382WPTT\_MSDS\_ENGUSA\_003.pdf

Page 9 of 9

165632  
REX LUMBER COMPANY  
CONNECTICUT YARD  
489 SULLIVAN AVE.  
SOUTH WINDSOR CT, 06074  
MSDS ENCLOSED



BEHLEN



KLUMPP

PLEASE NOTE MSDSs ARE NOW AVAILABLE THROUGH ELECTRONIC MEDIA.

E-mail your request to change the way you receive your MSDSs to [msds@rpmwfg.com](mailto:msds@rpmwfg.com).

Mailing Address: PO Box 22000 Hickory, North Carolina 28603  
Street Address: 3194 Hickory Boulevard Hudson, North Carolina 28638  
Phone: 828-728-8266  
Fax: 828-726-8128  
E-mail Address: [msds@rpmwfg.com](mailto:msds@rpmwfg.com)

Attention Safety Director:

Unless you have specified electronic format, paper copies of your requested product Material Safety Data Sheets (MSDSs) are appended.

Attachments to e-mail transmissions will appear in Adobe® PDF format. Adobe® Acrobat Reader may be obtained free from the Adobe® website.  
See: <http://www.adobe.com/products/acrobat/updatec.html>

If your MSDSs are on CD you may open the files by selecting the appropriate disk drive using your computer's file explorer. (Adobe® Acrobat Reader will again be needed.)

Please replace your existing copies with the appended as new information may have been added.

This communication and MSDSs are intended for the use of the addressee. If you did not request these documents, please advise us immediately by e-mail, fax, or telephone.

Regards,

MSDS Coordinator  
2/19/2009 11:43:18 AM

Enclosures  
7-GSP16382WPTT